

Projection Throw Chart

Screen Size 4:3

Screen Size*		Throw Distance*	
Diagonal*	Width*	Min*	Max*
30	24	34	40
60	48	70	83
80	64	95	111
100	80	119	139
120	96	143	167
150	120	179	210
200	160	240	280
300	240	361	422

Throw Ratio: 1.5 - 1.7:1 (distance : width)
*Measured in inches

Disclaimer: Please use this throw distance calculator for reference purpose only. For permanent installation purpose, we recommended that you assume 10% calculation margin of error or to test the unit on site.

Input/Output Terminals



3LCD Technology



Closed Captioning



Hitachi Trade-Up Program



AMX Device Discovery



Crestron Integrated Partner



3 Year Warranty

HDMI HDMI

Model Name	CP-X2521WN
Resolution	
RGB	1024 dots X 768 lines
Video	540 TV lines
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Colors	16.7 million colors
Aspect Ratio	Native 4:3/16:9 compatible
Lens	Manual zoom x 1.2
Throw Ratio (distance : width)	1.5-1.7 : 1
Lamp	215W @ Intelligent Eco Mode
Color Light Output	2,700 Lumens
White Light Output	2,700 Lumens
Expected Lamp Life	Approximately 3,000 hours (normal) 5,000 hours (Eco mode)*
Contrast Ratio	2000 : 1 (using active IRIS)
Speaker Output	1W
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	320W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	
RGB	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA, MAC 16"
Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
Component Video	480i, 576i, 480p, 720p, 1080i, 1080p
Acoustic Noise Level	37 dB (30 dB in Eco Mode)
H-Sync	15 Hz - 106 Hz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL, C-UL, FCC, CE, RoHS
RGB Input	
Analog RGB	15pin Mini-Dsub x 2
RGB Output	
RGB	15pin Mini-Dsub x 1
Digital Input	HDMI x 1 (HDCP Compliant)
Video Input	
S-Video	Mini DIN 4-pin connector x 1
Composite Video	RCA jack x 1
Component Video	15 pin D-Sub shrink x 2
Audio	
Input	3.5mm Stereo mini jack x 2: allocable
Output	3.5mm Stereo mini jack x 1
Ethernet	RJ-45 port / 100 base-T
Wireless	Optional Wireless 802.11n/g/b Capabilities
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Other	USB-A, USB-B (USB Mouse), PC-Less Presentation
Dimensions (W x D x H)	12.05" x 8.7" x 3.03"
Weight	5.1 lbs.
Closed Caption	CC1, CC2, CC3, CC4. T1, T2, T3, T4
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label
Optional Accessories	USBWL11N - Wireless USB Key
Replacement Parts	
Lamp	CPX2021WNLAMP (DT01191) (Filter Included in Box)
Remote Control	HL02771
Filter	UX36761



Printed 8.11

All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2010 Hitachi America, Ltd. All Rights Reserved.

1.800.HITACHI
900 Hitachi Way, Chula Vista, CA 91914
www.hitachi-america.us/projectors



Find Hitachi Projectors on Facebook



Follow us on Twitter @HALprojectors



Hitachi Projectors are on YouTube