

# SKF-4700 (Y/B) / SKS-4700 (Y/B) / SKR-4700 (Y/B)

2-Way Bass Reflex Speakers/Center and Surround Speaker Package/Surround Back Speaker



## Bringing Pristine Clarity and Wide Dynamics into Any Home Theater

The 4700 speaker series has been designed to bring dynamism and low-frequency energy to your home theater. As well as reproducing the details of quality music, these speakers can deliver loud, complex audio signals, without sounding smeared or confused. The SKF-4700 front speakers have the size and capacity to handle any musical score or sound effect. And for the smooth panning of sounds and a completely immersive atmosphere, the SKS-4700 center/surround speaker package is up there with the very best available in home theater.

### FEATURES

#### SKF-4700 (Y/B) 2-Way Bass Reflex Speakers

- 12 cm OMF Diaphragm Cone Woofer x 2
- 2.5 cm Balanced-Dome Floating (Suspended Mount) Tweeter
- Die-Cast Aluminum Stabilizers to Prevent Vibrations
- Magnetically Shielded

#### SKS-4700 (Y/B) Center/Surround Speaker Package

##### SKC-4700 Center Speaker

- 12 cm OMF Diaphragm Cone Woofer x 2
- 2.5 cm Balanced-Dome Floating (Suspended Mount) Tweeter
- Magnetically Shielded

##### SKM-4700 Surround Speakers

- 10 cm Cone Woofer
- 2.5 cm Balanced-Dome Tweeter
- Wall-Mounting Capability

#### SKR-4700 (Y/B) Surround Back Speaker

- 10 cm Cone Woofer
  - 2.5 cm Balanced-Dome Tweeter
  - Wall-Mounting Capability
- (Sold individually)*

### SPECIFICATIONS

Speaker Type		Sensitivity	
Front (SKF-4700)	2-way, bass reflex	Front (SKF-4700)	89 dB/W/m
Center (SKC-4700)	2-way, bass reflex	Center (SKC-4700)	89 dB/W/m
Surround (SKM-4700)	2-way, bass reflex	Surround (SKM-4700)	81 dB/W/m
Surround Back (SKR-4700)	2-way, bass reflex	Surround Back (SKR-4700)	81 dB/W/m
Drivers		Max. Input Power	
Front (SKF-4700)	12 cm OMF diaphragm cone woofer x 2 2.5 cm balanced-dome floating tweeter	Front (SKF-4700)	130 W
Center (SKC-4700)	12 cm OMF diaphragm cone woofer x 2 2.5 cm balanced-dome floating tweeter	Center (SKC-4700)	130 W
Surround (SKM-4700)	10 cm cone woofer 2.5 cm balanced-dome tweeter	Surround (SKM-4700)	130 W
Surround Back (SKR-4700)	10 cm cone woofer 2.5 cm balanced-dome tweeter	Surround Back (SKR-4700)	130 W
Frequency Response		Nominal Impedance	
Front (SKF-4700)	50 Hz-40 kHz	Front (SKF-4700)	8 Ω
Center (SKC-4700)	60 Hz-40 kHz	Center (SKC-4700)	8 Ω
Surround (SKM-4700)	50 Hz-50 kHz	Surround (SKM-4700)	8 Ω
Surround Back (SKR-4700)	50 Hz-50 kHz	Surround Back (SKR-4700)	8 Ω
Crossover Frequency		GENERAL	
Front (SKF-4700)	4.5 kHz	<b>Dimensions (W x H x D)</b>	
Center (SKC-4700)	4.5 kHz	Front (SKF-4700)	289 x 1032 x 309 mm
Surround (SKM-4700)	6 kHz	Center (SKC-4700)	433 x 157 x 194 mm
Surround Back (SKR-4700)	6 kHz	Surround (SKM-4700)	155 x 266 x 140 mm
		Surround Back (SKR-4700)	155 x 266 x 140 mm
		Weight	
		Front (SKF-4700)	8.8 kg
		Center (SKC-4700)	3.9 kg
		Surround (SKM-4700)	1.8 kg
		Surround Back (SKR-4700)	1.8 kg

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. OMF is a trademark of Onkyo Corporation.